

GOLDEN BITUMEN

Product Description:

A solvent based, general purpose, bituminous black paint for waterproofing and weather protecting of steelwork, asphalt, wood and concrete. When dry it forms an odorless and taint-free bitumen film.

Substrate:

It is suitable for application to a wide variety of surfaces including steel, iron, lead, zinc, aluminum, concrete, stone and brick.

Properties:

Waterproof
 Weatherproof
 Corrosion resistant protective coating



Physical properties:

General look	Matt
Color	Black
Specific weight	1.20 ± 0.05
Solid size	90 ± 2%
Dry layer thickening	150 microns
Theoretical spread rate	0.75 m ² / L
Pack size	5 KG – 13 KG



**GOLDEN
PAINTS**

الشركة الذهبية للصناعات الكيماوية
GOLDEN CHEMICAL INDUSTRIES CO.



Drying time:

Surface dry 24 hours	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

Surface Preparation:

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and protrusions.

Instructions for use:

The paint should be stirred well before use.

Sufficient amount of thinner may be added to obtain the appropriate viscosity for the application.

Do not paint over wet surfaces until after they are completely dry. taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and dehydration.

Application tools: Brush and spray.

Diluent:

Thinner 903

Thinning ratio: 10-20%.

Storage conditions:

Shelf life: Three year from the date of production.



Jordan



+962 79 721 9999



+962 79 781 1666



info@gcijo.com



www.gcipaints.com