

GOLDEN BONDING SEALER

Product Description:

A transparent water - base coat based on acrylic polymers, used for both interior and exterior surfaces, with high adhesion strength.

Usage:

Used for interior and exterior coatings over concrete, cement and gypsum surfaces.

Properties:

Excellent adhesion.
Suitable for all building materials surfaces.
Good alkaline resistance.



Physical properties:

General look	Matt
Color	transparent
Specific weight	1.00 ± 0.05 ASTM D1475
Solid size	24 ± 2% ASTM D2697
Dry layer thickening	25 microns
Theoretical spread rate	10 m ² / L



Drying time:

Surface dry	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

Surface Preparation:

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and protrusions.

Instructions for use:

The paint should be stirred well before use.

A suitable amount of water can be added to get reasonable viscosity for application.

Do not paint over wet surfaces until after they are completely dry.

Do Not to paint the next layer unless the previous layer is completely dry, taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and drying.

Application tools: brush and spray.

Diluent:

Thinner 144

Thinning ratio: 10-20%.

Storage conditions:

The container be kept in sealed, dry, cool, well ventilated place & stored in accordance with local regulation.

Shelf life: one year from the date of production.