شـركـة الذهبيــة للصناعـات الكـيماويـة .GOLDEN CHEMICHAL INDUSTRIES CO



GOLDEN EMULSION

Product Description:

A high quality water-based paint based on acrylic polymers and high quality colored materials. After application, it gives a smooth, uniformly white surface. It also gives long-term protection for internal surfaces. It is characterized by high resistance to different weather conditions with a high rate of hiding power.

Usage:

It is used for interior applications over concrete, cement and gypsum surfaces.

Properties:

High hiding power.

Super smoothness.

Easy to apply without spattering.

Excellent adhesion.

Suitable for all building materials surfaces.

Good alkaline resistance.

Good washability.

Certifications:

Conforming to Jordanian standard specification 31/2021



شـركـة الذهبيــة للصناعـات الكـيماويـة .GOLDEN CHEMICHAL INDUSTRIES CO





Physical properties:

General look	Matte
Color	white and other color as per golden color card
Specific weight	1.50 ± 0.05 ASTM D1475
Solid size	38 ± 2% ASTM D2697
Dry layer thickening	40-50 microns
Theoretical spread rate	8-10 m2 / L



Drying time:

Surface dry	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

Surface Preparation:

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and protrusions.

Instructions for use:

- •The paint should be stirred well before use.
- •A sitabile amount of water can be added to get resonable viscosity for application.
- •Do not paint over wet surfaces until after they are completely dry.
- •Do Not to paint the next layer untill the previous layer is completely dry, taking into account the minimum time between the two coats.
- •Adequate ventilation should be provided during application and drying.

شركة الذهبيـة للصناعـات الكيماويـة GOLDEN CHEMICHAL INDUSTRIES CO.



Application tools: roller, brush and spray.

Diluent: water.

Dilution percentage: 20-30%.

Storage conditions:

The container be kept in sealed, dry, cool, well ventilated place & stored in accordance with local regulation.

Shelf life: one year from the date of production.





