

GOLDEN ROOF COATING

Product Description:

A flexible, high-performance surface waterproofing based on acrylic polymers, characterized by high flexibility and water resistance.

The use:

It is used for exterior applications as an insulating layer for upper surfaces over concrete and cement surfaces.

Properties:

High resistance to water leakage.
Water vapor is allowed to escape from surfaces
Excellent adhesion.
High resistance to harsh weather conditions.



Physical properties:

| | |
|-------------------------|-------------------------|
| General look | Semi matt |
| Color | white |
| Specific weight | 1.27 ± 0.05 ASTM D1475 |
| Solid size | 48 ± 2% ASTM D2697 |
| Dry layer thickening | 40-50 microns |
| Theoretical spread rate | 8-10 m ² / L |



Drying time:

| | |
|----------------|---------------|
| Surface dry | 30-60 minutes |
| Hard dry | 2- 4 hours |
| Re-application | 8 hours |
| Complete dry | 48 hours |

Surface Preparation:

Surfaces must be clean, dry, and free from dirt, dust, grease, oils, salts, mold, and cement residues.

Instructions for use:

The paint should be stirred well before use.

A suitable amount of water can be added to get reasonable viscosity for application.

Do not paint over wet surfaces until after they are completely dry.

Do not to paint the next layer unless the previous layer is completely dry, taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and drying.

Application tools: brush and spray.

Diluent:

Diluent: water.

Dilution percentage: 20-30%.

Storage conditions:

The container be kept in sealed, dry, cool, well ventilated place & stored in accordance with local regulation.

Shelf life: one year from the date of production.