

## GOLDEN TEX

### Product Description:

A high quality final rough spray paint, based on acrylic polymers, which is characterized by its resistance to weather conditions.

### The use:

It is used for interior and exterior coatings over concrete, cement and gypsum surfaces.

### Properties:

Resistant to weather conditions.  
Excellent adhesion.  
Good water resistance.  
High durability.



### Physical properties:

General look	Matt
Color	white & other color as per golden color card
Specific weight	1.70 ± 0.05 ASTM D1475
Solid size	62 ± 2% ASTM D2697
Dry layer thickening	300-600 microns
Theoretical spread rate	1-2 m <sup>2</sup> / L



### Drying time:

Surface dry	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

#### Surface Preparation:

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and protrusions.

#### Instructions for use:

The paint should be stirred well before use.

A suitable amount of water can be added to get reasonable viscosity for application.

Do not paint over wet surfaces until after they are completely dry.

Do Not to paint the next layer until the previous layer is completely dry, taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and drying.

**Application tools:** brush and spray.

#### Diluent:

Diluent: water.

Dilution percentage: 5%.

#### Storage conditions:

The container be kept in sealed, dry, cool, well ventilated place & stored in accordance with local regulation.

Shelf life: one year from the date of production.