

GOLDEN VINYL SILK

Product Description:

A high quality water-based paint based on high quality polymers and coloring materials. After application, it gives a smooth, shiny, even white surface. It also gives long lasting protection for interior surfaces. It is characterized by high resistance to different weather conditions and easy removal of stains and dirt also the ability to wash with soap and water.

The use:

It is used for interior applications over concrete, cement and gypsum surfaces.

Properties:

- Unique hiding power.
- Super smoothness.
- Easy to apply without spattering.
- Excellent adhesion .
- Suitable for all building materials surfaces.
- Good alkaline resistance.
- Excellent continuous washability.

Certifications:

Conforming to Jordanian standard specification 31/2021





Physical properties:

General look	Semi - gloss
Color	white and other color as per golden color card
Specific weight	1.20 ± 0.05 ASTM D1475
Solid size	38 ± 2% ASTM D2697
Dry layer thickening	40-50 microns
Theoretical spread rate	8-10 m ² / L



Drying time:

Surface dry	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

Surface Preparation:

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and protrusions.

Instructions for use:

The paint should be stirred well before use.

A suitable amount of water can be added to get reasonable viscosity for application.

Do not paint over wet surfaces until after they are completely dry.

Do Not to paint the next layer until the previous layer is completely dry, taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and drying.

Application tools: roller, brush and spray.

Diluent: water.

Dilution percentage: 20-30%.

Storage conditions:

The container be kept in sealed, dry, cool, well ventilated place & stored in accordance with local regulation.

Shelf life: one year from the date of production.