

## GOLDEN WALL PUTY

### Product Description:

High-quality water-based putty, which is based on a special formula. Designed to provide smooth surfaces.

### The use:

It is used for interior applications over concrete, cement, and gypsum surfaces, and after sanding gives a smooth surface.

### Properties:

Excellent filling for hall & cracks.  
smoothness after sanding.  
Ease of application.  
Excellent adhesion & sanding.  
Excellent resistance to shrinkage.



### Physical properties:

General look	Matt
Color	White
Specific weight	1.70 ± 0.05 ASTM D1475
Solid size	50 ± 2% ASTM D2697
Dry layer thickening	100 microns
Theoretical spread rate	3 m <sup>2</sup> / l



### Drying time:

Surface dry	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

### Surface Preparation:

The surface must be cohesive and free from holes, pits, bumps and any fragile areas. All excess areas must be removed and make sure that the surface is clean, dry and free of dirt, dust, grease, oils, salts and mold.

### Instructions for use:

The paint should be stirred well before use.

A Suitable amount of water can be added to get reasonable viscosity for application.

Do not paint over wet surfaces until after they are completely dry.

Do Not to paint the next layer until the previous layer is completely dry, taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and drying.

**Application tools:** brush and spray.

### Diluent:

Diluent: water.

Dilution ratio: No dilution is required.

### Storage conditions:

The container be kept in sealed, dry, cool, well ventilated place & stored in accordance with local regulation.

Shelf life: one year from the date of production.