

GOLDEN WHEATHER SHIELD

Product Description:

A high-quality water-based paint based on special polymers and high-quality coloring materials. After application, give a uniform smooth white surface. It also gives long-term protection for outdoor surfaces. It is characterized by its high resistance to various weather conditions.

The use:

It is used for interior and exterior applications over concrete, cement and gypsum surfaces

Properties:

Resistant to alkaline and UV rays.
Excellent adhesion .
Smooth smooth.
Excellent hiding power.
Ease of application.



Physical properties:

General look	Semi - matt
Color	White according to the colors supported in the catalog
Specific weight	1.30 ± 0.05 ASTM D1475
Solid size	48 ± 2% ASTM D2697
Dry layer thickening	50 microns
Theoretical spread rate	11 m ² / l



Drying time:

Surface dry	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

Surface Preparation:

The surface must be cohesive and free from holes, pits, bumps and any fragile areas. All excess areas must be removed and make sure that the surface is clean, dry and free of dirt, dust, grease, oils, salts and mold.

Instructions for use:

The paint should be stirred well before use.

A suitable amount of water can be added to get reasonable viscosity for application.

Do not paint over wet surfaces until after they are completely dry.

Do Not to paint the next layer until the previous layer is completely dry, taking into account the minimum time between the two coats.

Adequate ventilation should be provided during application and drying.

Application tools: brush and spray.

Diluent:

Diluent: water.

Thinning ratio: 20-30%

Storage conditions:

The container be kept in sealed, dry, cool, well ventilated place & stored in accordance with local regulation.

Shelf life: one year from the date of production.