

GOLDEN CLEANING THINNER

Product Description:

A mixture of fast evaporating solvents to clean oils and solvents, tools and equipment.

Substrate:

It is used for cleaning spray equipment and tools.

Properties:

For cleaning oils and solvents.

Excellent for cleaning equipment.



Physical properties:

Color	Transparent.
Specific weight	0.85 ± 0.05
Flash Point	4-10 °C
Solid size	0 ± 0%
Dry layer thickening	40 microns
V.O.C	870 gm/ Ltr
Pack size	1 LTR - 4 LTR - 150 LTR



**GOLDEN
PAINTS**

الشركة الذهبية للصناعات الكيماوية
GOLDEN CHEMICAL INDUSTRIES CO.



Drying time:

Surface dry 24 hours	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

Surface Preparation:

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and protrusions.

Instructions for use:

- The paint should be stirred well before use.
- Sufficient amount of thinner may be added to obtain the appropriate viscosity for the application.
- Do not paint over wet surfaces until after they are completely dry. taking into account the minimum time between the two coats.
- Adequate ventilation should be provided during application and dehydration.

Application tools: brush and spray.

Diluent:

None

Storage conditions:

Shelf life: One year from the date of production.