



**GOLDEN
PAINTS**

الشركة الذهبية للصناعات الكيماوية
GOLDEN CHEMICAL INDUSTRIES CO.

GOLDEN HUMMER FINISH

Product Description:

A quick drying coating based on special resins, aluminum paste and additives, which gives uniform hammer pattern, where hides the minor defects and surface imperfections.

Substrate:

It is used for metal furniture, machinery parts electrical boards, tools and equipment.

Features:

Easy to supply.
High quality finish.
Excellent hiding power.
Quick drying.



Physical properties:

General look	Glossy
Color	White & according to Hammer Finish catalogue
Specific weight	1.00 ± 0.05
Solid size	54 ± 2%
Dry layer thickening	50 Microns.
Theoretical spread rate	10-12 m ² / L
Packing size	1 LTR, 3.6 LTR



**GOLDEN
PAINTS**

الشركة الذهبية للصناعات الكيماوية
GOLDEN CHEMICAL INDUSTRIES CO.



Drying time:

Surface dry 24 hours	30-60 minutes
Hard dry	2- 4 hours
Re-application	6 hours
Complete dry	24 hours

Surface Preparation:

The surface must be clean, free of grease, oils, dust and suspended matter, and cement surfaces must be completely dry, and the surface must be cohesive, free from defects and protrusions.

Instructions for use:

- The paint should be stirred well before use.
- Sufficient amount of thinner may be added to obtain the appropriate viscosity for the application.
- Do not paint over wet surfaces until after they are completely dry.
- Taking into account the minimum time between the two coats.
- Adequate ventilation should be provided during application and dehydration.

Application tools: Brush and Spray gun.

Diluent:

Thinner 144

Thinning ratio: 10-20%.

Storage conditions:

Shelf life: Three year from the date of production.



Jordan



+962 79 721 9999



+962 79 781 1666



info@gcijo.com



www.gcipaint.com